

DUMPER SERIE 1500H




Diesel Engine	KOHLER
Power	25,5 CV
N° cylinders	4
Cooling	Water cooler
Emission Standards	Stage V

Transmission	Hydrostatic 4x4 by 4 wheels drive with anti-skating system																
Brakes	Service: Hydrostatic / Parking: Oil bath bearing with electric activation																
Steering	Hydraulic																
Chassis	Rigid																
Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.																
Wheels	<table border="0"> <tr> <td>Front</td> <td colspan="5">11,0 / 65 - 12".</td> </tr> <tr> <td>Rear</td> <td colspan="5">11,0 / 65 - 12".</td> </tr> </table>					Front	11,0 / 65 - 12".					Rear	11,0 / 65 - 12".				
Front	11,0 / 65 - 12".																
Rear	11,0 / 65 - 12".																
Outer Turning Radius	395 cm																
Tanks	<table border="0"> <tr> <td>Oil</td> <td colspan="5">34 L</td> </tr> <tr> <td>Fuel</td> <td colspan="5">28 L</td> </tr> </table>					Oil	34 L					Fuel	28 L				
Oil	34 L																
Fuel	28 L																
Hopper	D-1500H	D-1500H-AC	D-1500H-DG	D-1500H-AG	D-1750H-DA												
Water level	617 L	606 L	678 L	678 L	702 L												
Level	908 L	887 L	871 L	871 L	1.039 L												
Working Load	D-1500H 1.500 Kg	D-1500H-AC 1.500 Kg	D-1500H-DG 1.500 Kg	D-1500H-AG 1.500 Kg	D-1750H-DA 1.750 Kg												
Maximum trailer load (Optional Hook)	D-1500H	D-1500H-AC	D-1500H-DG	D-1500H-AG	D-1750H-DA												
Without Brakes	700 Kg	800 Kg	800 Kg	900 Kg	800 Kg												
With Brakes	1.450 Kg	1.600 Kg	1.600 Kg	1.800 Kg	1.600 Kg												
Unladen Weight	D-1500H 1.460 Kg	D-1500H-AC 1.680 Kg	D-1500H-DG 1.695 Kg	D-1500H-AG 1.915 Kg	D-1750H-DA 1.680 Kg												
Equipment	Joystick multifunction. Flashing beacon. Seat belt. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal.																
Security	Roll-cage / Safety roof																
Options	Windscreen and windscreen wipers. Homologated Lights. Seat belt with micro Passenger seat Closed Cabin. Air Conditioning. Heating. Hook. Folding protector arch. Wheels 10.0/75-15.3". Snowplow. * Salt spreader. * Water tank 350 Litres. * High Pressure Kit. Disinfection / fumigation Kit. * (*Only self-loading version)																
Maximum speed	Standard Wheel: 20 Km/h – Optional Wheel: 22,5 Km/h																

D-1500H

Frontal Unloading Hydrostatic Dumper at 798 mm




Dimensions (mm)

- A – 2.785 Maximum length
- B – 1.675 Wheelbase
- C – 485 Rear extension
- D – 2.265 Maximum height
- F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient: 47-43%* (* With optional wheel: 10.0/75-15.3" 10 PR)

D-1500H-AC

Hydrostatic Self-loading and Frontal Unloading Dumper at 798 mm




Dimensions (mm)

- A – 3.890 Maximum length
- B – 1.675 Wheelbase
- C – 485 Rear extension
- D – 2.265 Maximum height
- F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 45-41%* (*With optional wheel: 10.0/75-15.3" 10 PR). Shovel capacity: 160 L

D-1500H-DG

Hydrostatic Dumper with Swivel Unloading at 900 mm




Dimensions (mm)

- A – 3.120 Maximum length
- B – 1.675 Wheelbase
- C – 485 Rear extension
- D – 2.265 Maximum height
- F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 45-41%* (*With optional wheel: 10.0/75-15.3" 10 PR). Hopper angle: 180° Both directions

D-1500H-AG

Hydrostatic Self-loading and Swivel Unloading Dumper at 900mm




Dimensions (mm)

- A – 3.890 Maximum length
- B – 1.675 Wheelbase
- C – 485 Rear extension
- D – 2.265 Maximum height
- F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 47-41%* (*With optional wheel: 10.0/75-15.3" 10 PR). Hopper angle: 180° Both directions
Shovel capacity: 160 L

D-1750H-DA

Hydrostatic Dumper with High Unloading at 1.685 mm



Dimensions (mm)

- A – 2.950 Maximum length
- B – 1.675 Wheelbase
- C – 485 Rear extension
- D – 2.265 Maximum height
- F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 41.5-37%* (*With optional wheel: 10.0/75-15.3" 10 PR)