FORKLIFT CA-1500/1500T4

Diesel Engine Power KOHLER KDW 1003 24,5 CV 3

 N° cylinders
 3


 Cooling
 Water cooler

 Emission Standards
 Stage V



CA-1500 / 1500T4

Forklift



Dimensions (mm)

A - 3.800 Maximum length

B - 1.720 Wheelbase

C - 420 Rear extension

D - 2.040 Maximum height F - 1.240 Maximum width

Front track width: 960 Front track width: 1.000







Emission Standards	Stage V		
Transmission	Mechanical front traction by Cardan (CA-1500)		
	Mechanical traction 4x4 by Cardan (CA-1500T4)		
Gearbox	4+4 speeds with reverser		
Brakes	Hydraulics		
Clutch	Single dry plate		
Steering	Hydraulic		
Chassis	Rigid		
Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.		
Wheels	CA-1500	CA-1500T4	
Front	27 x 8,50 - 15"	27 x 8,50 - 15"	
Rear	6.00 - 9"	23 x 8.50 - 12"	
Outer Turning Radius	350 cm.		
Tanks			
Oil	30 L		
Fuel	25 L		
Working Load	1.500 kg		
Maximum elevation height	2.500 mm.		
Maximum gradient	44%		
Unladen Weight	2.420 kg		
Equipment	Flashing Beacon. Seat belt. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal. Load guard. Sideshift and forks.		
Security	Roll-cage / Safety roof		
Options	Homologated Lights. Seat belt with micro. Windscreen and windscreen wipers.		

Mast 1.500 Kg at 2.000 mm. Mast1.300 Kg at 3.200 mm.