

# DUMPER SERIE 1500H



Diesel Engine	KOHLER
Power	25,5 CV
N° cylinders	4
Cooling	Water cooler
Emission Standards	Stage V

Transmission	Hydrostatic 4x4 by 4 wheels drive with anti-skating system
Brakes	Service: Hydrostatic / Parking: Oil bath bearing with electric activation

Steering	Hydraulic
----------	-----------

Chassis	Rigid
---------	-------

Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.
-------------	--

Wheels	
Front	11,0 / 65 - 12".
Rear	11,0 / 65 - 12".

Outer Turning Radius	395 cm
----------------------	--------

Tanks	
Oil	34 L
Fuel	28 L

Hopper	D-1500H	D-1500H-AC	D-1500H-DG	D-1500H-AG	D-1750H-DA
Water level	617 L	606 L	678 L	678 L	702 L
Level	908 L	887 L	871 L	871 L	1.039 L

Working Load	D-1500H	D-1500H-AC	D-1500H-DG	D-1500H-AG	D-1750H-DA
	1.500 Kg	1.500 Kg	1.500 Kg	1.500 Kg	1.750 Kg

Maximum trailer load (Optional Hook)	D-1500H	D-1500H-AC	D-1500H-DG	D-1500H-AG	D-1750H-DA
Without Brakes	700 Kg	800 Kg	800 Kg	900 Kg	800 Kg
With Brakes	1.450 Kg	1.600 Kg	1.600 Kg	1.800 Kg	1.600 Kg

Unladen Weight	D-1500H	D-1500H-AC	D-1500H-DG	D-1500H-AG	D-1750H-DA
	1.460 Kg	1.680 Kg	1.695 Kg	1.915 Kg	1.680 Kg

Equipment	Joystick multifunction. Flashing beacon. Seat belt. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal.
-----------	---


Security	Roll-cage / Safety roof
----------	-------------------------

Options	Windscreen and windscreen wipers. Homologated Lights. Seat belt with micro Passenger seat Closed Cabin. Air Conditioning. Heating. Hook. Folding protector arch. Wheels 10.0/75-15.3". Snowplow. * Salt spreader. * Water tank 350 Litres. * High Pressure Kit. Disinfection / fumigation Kit. * (*Only self-loading version)
---------	---

Maximum speed	Standard Wheel: 20 Km/h – Optional Wheel: 22,5 Km/h
---------------	---

## D-1500H

Frontal Unloading Hydrostatic Dumper at 798 mm




Dimensions (mm)

- A – 2.785 Maximum length
  - B – 1.675 Wheelbase
  - C – 485 Rear extension
  - D – 2.265 Maximum height
  - F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient: 47-43%\* (\* With optional wheel: 10.0/75-15.3" 10 PR)

## D-1500H-AC

Hydrostatic Self-loading and Frontal Unloading Dumper at 798 mm




Dimensions (mm)

- A – 3.890 Maximum length
  - B – 1.675 Wheelbase
  - C – 485 Rear extension
  - D – 2.265 Maximum height
  - F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 45-41%\* (\*With optional wheel: 10.0/75-15.3" 10 PR). Shovel capacity: 160 L

## D-1500H-DG

Hydrostatic Dumper with Swivel Unloading at 900 mm




Dimensions (mm)

- A – 3.120 Maximum length
  - B – 1.815 Wheelbase
  - C – 485 Rear extension
  - D – 2.265 Maximum height
  - F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 45-41%\* (\*With optional wheel: 10.0/75-15.3" 10 PR). Hopper angle: 180° Both directions

## D-1500H-AG

Hydrostatic Self-loading and Swivel Unloading Dumper at 900mm




Dimensions (mm)

- A – 3.890 Maximum length
  - B – 1.815 Wheelbase
  - C – 485 Rear extension
  - D – 2.265 Maximum height
  - F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 47-41%\* (\*With optional wheel: 10.0/75-15.3" 10 PR). Hopper angle: 180° Both directions  
Shovel capacity: 160 L

## D-1750H-DA

Hydrostatic Dumper with High Unloading at 1.685 mm



Dimensions (mm)

- A – 2.950 Maximum length
  - B – 1.675 Wheelbase
  - C – 485 Rear extension
  - D – 2.265 Maximum height
  - F – 1.725 Maximum width
- Front track width / posterior: 1.470 / 1.370

Maximum gradient 41.5-37%\* (\*With optional wheel: 10.0/75-15.3" 10 PR)