

# DUMPER SERIE 1750T4




Diesel Engine	KOHLER KDW 1003
Power	24,5 CV
N° cylinders	3
Cooling	Water cooler
Emission Standards	Stage V

Transmission	Mechanical traction 4x4 by Cardan				
Gearbox	4+4 speeds with reverser				
Brakes	Hydraulics a las 4 Wheels				
Clutch	Single dry plate				
Steering	Hydraulic				
Chassis	Rigid				
Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.				
Wheels					
Front	27 x 8,50 - 15"				
Rear	27 x 8,50 - 15"				
Outer Turning Radius	380 cm.				
Tanks					
Oil	34 L				
Fuel	28 L				
Hopper	D-1750T4	D-1750T4-AC	D-1750T4-DA	D-1750T4-DG	D-1750T4-AG
Water level	617 L	606 L	702 L	678 L	678 L
Level	908 L	887 L	1.039 L	871 L	871 L
Working Load	1.750 kg				
Maximum trailer load (Optional Hook)	D-1750T4	D-1750T4-AC	D-1750T4-DA	D-1750T4-DG	D-1750T4-AG
Without Brakes	600 Kg	730 Kg	730 Kg	730 Kg	730 Kg
With Brakes	1.350 Kg	1.550 Kg	1.550 Kg	1.570 Kg	1.570 Kg
Unladen Weight	1.370 kg	1.615 Kg.	1.590 kg	1.610 Kg.	
Equipment	Flashing beacon. Seat belt. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal.				
Security	Roll-cage / Safety roof				
Options	Windscreen and windscreen wipers. Homologated Lights. Hydraulic hammer. Passenger seat. Seat belt with micro. Hook. Folding protector Arch. Disinfection / fumigation Kit. * Rear water tank: 350L.* (*Only self-loading version)				
Maximum speed	20 Km/h				

## D-1750T4

Frontal Hydraulic Unloading Dumper at 785 mm




Dimensions (mm)

A – 2.780 Maximum length  
B – 1.670 Wheelbase  
C – 530 Rear extension  
D – 2.230 Maximum height  
F – 1.660 Maximum width  
Front track width: 1.240  
Rear track width: 1.240

Maximum gradient: 55%

## D-1750T4-AC

Self-loading and Frontal Hydraulic Unloading Dumper at 785 mm




Dimensions (mm)

A – 3.890 Maximum length  
B – 1.670 Wheelbase  
C – 530 Rear extension  
D – 2.230 Maximum height  
F – 1.660 Maximum width  
Front track width: 1.240  
Rear track width: 1.240

Maximum gradient: 51%. Shovel capacity: 160 L

## D-1750T4-DA

High Unloading Dumper at 1.710 mm




Dimensions (mm)

A – 2.950 Maximum length  
B – 1.670 Wheelbase  
C – 530 Rear extension  
D – 2.230 Maximum height  
F – 1.660 Maximum width  
Front track width: 1.240  
Front track width: 1.240

Maximum gradient: 51%

## D-1750T4-DG

Swivel Unloading Dumper at 785 mm




Dimensions (mm)

A – 2.880 Maximum length  
B – 1.670 Wheelbase  
C – 530 Rear extension  
D – 2.230 Maximum height  
F – 1.660 Maximum width  
Front track width: 1.240  
Front track width: 1.240

Maximum gradient: 51%. Hopper angle: 180° Both directions

## D-1750T4-AG

Self-loading and Swivel Unloading Dumper at 785 mm



Dimensions (mm)

A – 3.890 Maximum length  
B – 1.670 Wheelbase  
C – 530 Rear extension  
D – 2.230 Maximum height  
F – 1.660 Maximum width  
Front track width: 1.240  
Front track width: 1.240

Maximum gradient: 49%. Hopper angle: 180° Both directions. Shovel capacity: 160 L