


DUMPER SERIE 2000H



Diesel Engine	KOHLER			
Power	25,5 CV			
N° cylinders	4			
Cooling	Water cooler			
Emission Standards	Stage V			
Transmission	Hydrostatic 4x4 by 4 wheels drive with anti-skating system			
Brakes	Service: Hydrostatic / Parking: Oil bath bearing with electric activation			
Steering	Hydraulic			
Chassis	Rigid			
Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.			
Wheels				
Front	11,0 / 65 - 12"			
Rear	11,0 / 65 - 12"			
Outer Turning Radius	395 cm			
Tanks				
Oil	34 L			
Fuel	28 L			
Hopper	D-2000H	D-2000H-AC	D-2000H-DG	D-2000H-AG
Water level	660 L	660 L	650 L	650 L
Level	980 L	980 L	965 L	965 L
Working Load	D-2000H 2.000 Kg	D-2000H-AC 2.000 Kg	D-2000H-DG 2.000 Kg	D-2000H-AG 2.000 Kg
Maximum trailer load (Optional Hook)	D-2000H	D-2000H-AC	D-2000H-DG	D-2000H-AG
Without Brakes	700 Kg	800 Kg	800 Kg	900 Kg
With Brakes	1.450 Kg	1.600 Kg	1.600 Kg	1.800 Kg
Unladen Weight	D-2000H 1.460 Kg	D-2000H-AC 1.680 Kg	D-2000H-DG 1.695 Kg	D-2000H-AG 1.915 Kg
Equipment	Joystick multifunction. Flashing beacon. Seat belt with micro. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal.			
Security	Roll-cage / Safety roof			
Options	Windscreen and windscreen wipers. Homologated Lights. Seat belt with micro Passenger seat Closed Cabin. Air Conditioning. Heating. Hook. Folding protector arch. Wheels 10.0/75-15.3". Snowplow. * Salt spreader. * Water tank 350 Litres. * High Pressure Kit. Disinfection / fumigation Kit. * 2 Speeds (*Only self-loading version)			
Maximum speed	Standard Wheel: 20 Km/h – Optional Wheel: 22,5 Km/h			

D-2000H

Frontal Unloading Hydrostatic Dumper at 798 mm




Dimensions (mm)

A – 2.785 Maximum length
B – 1.675 Wheelbase
C – 485 Rear extension
D – 2.265 Maximum height
F – 1.725 Maximum width
Front track width: 1.470
Front track width: 1.370

Maximum gradient: 41-37%* (* With optional wheel: 10.0/75-15.3" 10 PR)

D-2000H-AC

Hydrostatic Self-loading and Frontal Unloading Dumper at 798 mm




Dimensions (mm)

A – 3.890 Maximum length
B – 1.675 Wheelbase
C – 485 Rear extension
D – 2.265 Maximum height
F – 1.725 Maximum width
Front track width: 1.470
Front track width: 1.370

Maximum gradient 39-35%* (* With optional wheel: 10.0/75-15.3" 10 PR). Shovel capacity: 160 L

D-2000H-DG

Hydrostatic Dumper with Swivel Unloading at 900 mm




Dimensions (mm)

A – 3.120 Maximum length
B – 1.675 Wheelbase
C – 485 Rear extension
D – 2.265 Maximum height
F – 1.725 Maximum width
Front track width: 1.470
Front track width: 1.370

Maximum gradient 39-35%* (* With optional wheel: 10.0/75-15.3" 10 PR). Hopper angle: 180° Both directions

D-2000H-AG

Hydrostatic Self-loading and Swivel Unloading Dumper at 900mm



Dimensions (mm)

A – 3.890 Maximum length
B – 1.675 Wheelbase
C – 485 Rear extension
D – 2.265 Maximum height
F – 1.725 Maximum width
Front track width: 1.470
Front track width: 1.370

Maximum gradient 36-32,5%* (* With optional wheel: 10.0/75-15.3" 10 PR). Hopper angle: 180° Both directions
Shovel capacity: 160 L