

DUMPER SERIE 3500H



| | |
|--------------------|-------------------|
| Diesel Engine | PERKINS 403J-E17T |
| Power | 49 CV |
| N° cylinders | 3 |
| Cooling | Water cooler |
| Emission Standards | Stage V |

| | |
|--------------|--|
| Transmission | Hydrostatic 4x4 by 4 wheels drive with anti-skating system. 2 gear |
| Brakes | Service: Hydrostatic by Inching. Parking and Emergency brake: Hydraulic oil bath |
| Steering | Hydraulic |
| Chassis | Rigid |
| Driver Seat | Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt. |

| | | | |
|----------------------|------------------|---------------------|---------------------|
| Wheels | Front | 11.5/80 -15,3"14 PR | |
| | Rear | 11.5/80 -15,3"14 PR | |
| Outer Turning Radius | D-3500H: 380 cm. | D-3500H-DG: 400 cm. | D-3500H-AG: 400 cm. |

| | | |
|-------|------|------|
| Tanks | Oil | 50 L |
| | Fuel | 35 L |

| | | | |
|--------|-------------|------------|------------|
| Hopper | D-3500H | D-3500H-DG | D-3500H-AG |
| | Water level | 1.380 L | 1.180 L |
| Level | 1.880 L | 1.830 L | 1.750 L |

| | | | |
|--------------|----------|----------|----------|
| Working Load | 3.500 kg | 3.500 kg | 3.500 kg |
|--------------|----------|----------|----------|

| | | | | |
|---|----------------|------------|------------|-----------|
| Maximum trailer load (Optional Hook) | D-3500H | D-3500H-DG | D-3500H-AG | |
| | Without Brakes | 1.150 Kg. | 1.250 Kg. | 1.500 Kg. |
| | With Brakes | 2.450 Kg. | 2.750 Kg. | 3.250 Kg. |

| | | | |
|----------------|----------|------------|------------|
| Unladen Weight | D-3500H | D-3500H-DG | D-3500H-AG |
| | 2.320 kg | 2.605 Kg | 3.080 Kg |

| | |
|-----------|--|
| Equipment | Joystick multifunction. Flashing beacon. Seat belt with micro. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal. Front camera. |
|-----------|--|


| | |
|----------|-------------------------|
| Security | Roll-cage / Safety roof |
|----------|-------------------------|

| | |
|---------|--|
| Options | Homologated Lights. Hydraulic Hammer. Passenger Seat. Seat Belt with micro. Windscreen and Windscreen wipers. Closed cabin Air conditioning. Heating. Hook |
|---------|--|

D-3500H-AG: Mast. Backhoe. Hydraulic hammer for Backhoe. Water tank de 350 litres/ 600 litres. Disinfection / fumigation Kit. Snowplow. Salt spreader. Brushcutter.

D-3500H

Frontal Unloading Hydrostatic Dumper at 1.100 mm




Dimensions (mm)
 A – 3.435 Maximum length
 B – 1.810 Wheelbase
 C – 750 Rear extension
 D – 2.640 Maximum height
 F – 1.810 Maximum width
 Front track width: 1.500
 Front track width: 1.500

Maximum gradient: 49%

D-3500H-DG

Hydrostatic Dumper with Swivel Unloading at 930 mm




Dimensions (mm)
 A – 3.580 Maximum length
 B – 1.950 Wheelbase
 C – 750 Rear extension
 D – 2.640 Maximum height
 F – 1.800 Maximum width
 Front track width: 1.500
 Front track width: 1.500

Maximum gradient: 47%. Hopper angle: 180° Both directions

D-3500H-AG

Hydrostatic Self-loading and Swivel Unloading Dumper at 970mm



Dimensions (mm)
 A – 4.840 Maximum length
 B – 1.950 Wheelbase
 C – 750 Rear extension
 D – 2.640 Maximum height
 F – 1.820 Maximum width
 Front track width: 1.500
 Front track width: 1.500

Maximum gradient: 47%. Hopper angle: 180° Both directions. Shovel capacity: 320 L.