

DUMPER SERIE 4500H




Diesel Engine	PERKINS 403J-E17T
Power	49 CV
N° cylinders	3
Cooling	Water cooler
Emission Standards	Stage V

Transmission	Hydrostatic 4x4 by 4 wheels drive with anti-skating system. 2 gear	
Brakes	Service: Hydrostatic by Inching. Parking and Emergency brake: Hydraulic oil bath	
Steering	Hydraulic	
Chassis	Rigid	
Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.	
Wheels		
Front	11.5/80 -15,3"14 PR	
Rear	11.5/80 -15,3"14 PR	
Outer Turning Radius	D-4500H: 380 cm.	D-4500H-DG: 400 cm.
Tanks		
Oil	50 L	
Fuel	35 L	
Hopper	D-4500H	D-4500H-DG
Water level	1.408 L	1.330 L
Level	2.050 L	2.004 L
Working Load	4.500 kg	
Maximum trailer load (Optional Hook)	D-4500H	D-4500H-DG
Without Brakes	1.150 Kg.	1.250 Kg.
With Brakes	2.450 Kg.	2.750 Kg.
Unladen Weight	D-4500H	D-4500H-DG
	2.320 kg	2.605 Kg
Equipment	Joystick multifunction. Flashing beacon. Seat belt with micro. Electrical Start and Stop. Left rear-view mirror. Reverse Warning Signal. Front camera.	
Security	Roll-cage / Safety roof	
Options	Homologated Lights. Hydraulic Hammer. Passenger seat. Seat belt with micro. Windscreen and windscreen wipers. Closed cabin. Air conditioning Heating. Hook.	

D-4500H

Frontal Unloading Hydrostatic Dumper at 1.100 mm




Dimensions (mm)

- A – 3.435 Maximum length
- B – 1.810 Wheelbase
- C – 750 Rear extension
- D – 2.640 Maximum height
- F – 1.850 Maximum width
- Front track width: 1.540
- Front track width: 1.500

Maximum gradient: 42%

D-4500H-DG

Hydrostatic Dumper with Swivel Unloading at 930 mm



Dimensions (mm)

- A – 3.620 Maximum length
- B – 1.950 Wheelbase
- C – 750 Rear extension
- D – 2.640 Maximum height
- F – 1.850 Maximum width
- Front track width: 1.540
- Front track width: 1.500

Maximum gradient: 40%. Hopper angle: 180° Both directions